

# ACRYLPACK-S

## KOLOUR KOAT TINT PACK

PRODUCT CODES: 007-ACP01 → 007-ACP12

### Solvent Based Tint Pack for Acrylic Sealers

CONCRETE STAIN SYSTEMS

ACRYLPACK-S

#### PRODUCT DESCRIPTION

**ACRYLPACK-S** is a high solids, concentrated, solvent based acrylic tint system specially formulated for solvent based acrylic sealers. **ACRYLPACK-S** is formulated with high quality, ultra fine particle pigments that easily disperses in solvent based acrylic sealers. **ACRYLPACK-S** is a superior choice to obtain a semi transparent stain or a solid opaque colored finish in most solvent based acrylic sealer systems.

#### BENEFITS/FEATURES

- ◆ An excellent choice of 14 colors (including black and white).
- ◆ Very economical and decorative way to seal a variety of concrete substrates.
  - ◆ Reduces the cost of inventory stocking needs
- ◆ Very easy way to stain, as opposed to multiple steps of other stain systems.

#### RECOMMENDED APPLICATIONS

**ACRYLPACK-S** is recommended for use on unsealed or untreated warehouse floors, garages, basements, docks, driveways, sidewalks, and any other concrete surface where a solid color sealing and dust proofing method is desired.

#### TECHNICAL INFORMATION

Solids (Diluted).....	Depends on the acrylic sealer used	Wet Appearance.....	Varies Depending Upon Color
Drying Time.....	1-2 hours	Dry Appearance.....	Varies, High Gloss
Re-Coat Time.....	4-24hours	VOC Content.....	N/A
Foot Traffic.....	4-6 hours	Blush Resistance.....	Good
Wheel Traffic.....	24-48 hours	Solvent Resistance.....	Minimal
Application Temp.....	40°F - 85°F	Concrete Adhesion.....	Excellent

\*\*\*Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

#### APPROXIMATE USAGE RATES

Desired Finish	Approximate amounts added per 1 gallon	Approximate amounts added per 5 gallons
Semi Transparent Stain	2 - 8 ounces	8 - 16 ounces
Solid Opaque Finish	8 ounces	32 ounces (1 quart)

\*Usage rates are suggested amounts only! Due to varying sealer compositions, substrates, surface texture, porosity and desired look a test area is recommended to achieve desired results.

#### SHELF LIFE

**ACRYLPACK-S** have a shelf life of a minimum of one year in it's original, sealed, unopened container.

#### PACKAGING

**ACRYLPACK-S** is packaged in quart cans only.



#### SURFACE KOATINGS, INC.

134 Davis St. Portland, TN 37148  
 Phone: (615) 323-9461 Fax: (615) 323-9816  
 Visit us online at: [www.SurfKcoat.com](http://www.SurfKcoat.com)

**INSTRUCTIONS FOR USE**

**MIXING:** Mix desired amount in a solvent based acrylic sealer for 1-2 minutes using a squirrel mixer prior to application. Allow any foam to settle prior to use. Material may separate during long term storage. Re-mix as needed.

**PLEASE NOTE:** It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Usage and coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc. If applying by spray method, extended coverage rates may be achieved, but be aware that less material will be applied and the transparency of the color may vary.

**CAUTION:** Do not add too much color! Apply a test area prior to job application for desired appearance. Over pigmenting may cause color float or streaking. Especially in the darker colors! Do not allow to puddle! The average usage is 1 quart (32 oz.) per 5 gallons of material for most opaque applications. For lighter colors it may take more and darker colors may take less depending on the application as well as the composition of the solvent based acrylic sealer.

Check **Acrylpack-S** for compatibility with the solvent based acrylic sealer to be used prior to use!

**CLEAN-UP**

Use Xylene. Dispose of containers in accordance with local and federal regulations.

**PRECAUTIONS AND LIMITATIONS**

- ▶ **ACRYLPACK-S** will not freeze during storage, however, allow temperature to rise to 50 degrees F prior to application.
- ▶ All HVAC ventilation ducts should be somehow blocked prior to application so solvents fumes are not distributed.
- ▶ Keep away from open flames. **ACRYLPACK-S** is flammable and is very susceptible to ignition.
- ▶ Follow the instructions for the solvent based acrylic sealer that is to be used for application guidelines.
- ▶ Coverage rates depend upon many conditions including application method, surface porosity, applicator, ect.
- ▶ **ACRYLPACK-S** was designed for new or old concrete and to be applied in thin coats, not one thick coat.
- ▶ Please be aware that the finished product when cured may be slippery when wet. Use anti-skid additive as needed.
- ▶ **ACRYLPACK-S** is not resistant to brake fluid, gasoline, and many similar products.
- ▶ It is not recommended to thin **ACRYLPACK-S**. Improper thinning may cause sealer to delaminate in a short time frame.

**SPECIAL NOTES**

Please consult Material Safety Data Sheet (MSDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 615-323-9461.

- ◆ For color selection, please request a **KOLOUR KOAT** color chart.

**SURFKOAT™****SURFACE KOATINGS, INC.**

134 Davis St. Portland, TN 37148  
Phone: (615) 323-9461 Fax: (615) 323-9816  
Visit us online at: [www.SurfKcoat.com](http://www.SurfKcoat.com)