

# GLU-GONE

PRODUCT CODE: 009-GLUGN

## WATER BASED CARPET GLUE AND MASTIC REMOVER

### PRODUCT DESCRIPTION

**Glu-Gone** is a safe, non-flammable water based carpet glue and mastic remover that effectively softens and removes most types of carpet adhesives and similar glue/adhesive deposits. **Glu-Gone** contains no chlorinated solvents, butyl solvents, or phosphates and only contains biodegradable surfactants. This product emulsifies glue and mastic by deeply penetrating and softening the adhesive to allow easy removal. This superior formula breaks down adhesives for removal so that new mastic, glue, or most any other form of coating can be applied after **Glu-Gone** application has dried.

### BENEFITS/FEATURES

- ◆ Easily softens and removes most types of carpet glue and mastic.
- ◆ Formulated as an economical means of removing adhesives as apposed to costly mechanical means.
  - ◆ Non-flammable and non-combustible formula.

### RECOMMENDED APPLICATIONS

**Glu-Gone** is recommended for removing carpet glue and mastic from all types of flooring surfaces.

### TECHNICAL INFORMATION

Solids.....0%	Wet Appearance.....Green
Drying Time.....Refer to Directions	Dry Appearance.....n/a
Re-Coat Time.....Refer to Directions	VOC Content.....<160 g/l
Foot Traffic.....Refer to Directions	Blush Resistance.....n/a
Wheel Traffic.....Refer to Directions	Solvent Resistance.....n/a
Application Temp.....40°F - 85°F	Concrete Adhesion.....n/a

\*\*\*Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

### SPECIFICATIONS/COMPLIANCES

**Glu-Gone** is VOC and OTC compliant in most areas of the United States and many foreign nations.

### APPROXIMATE COVERAGE RATES

<u>Application Surface</u>	<u>First Coat</u>	<u>Optional Second Coat</u>
Glue and Mastic floor surfaces	150-200 ft <sup>2</sup>	150-200 ft <sup>2</sup>

\*Coverage rates vary depending upon surface porosity and texture, and application method. Follow directions for best results.

### SHELF LIFE

**Glu-Gone** has a shelf life of one-two years in it's original, sealed, unopened container.

### PACKAGING

**Glu-Gone** is packaged and stocked in 1 gallon jugs (Also available in 5 gallon pails, and 55 gallon drums)

**SURFKOAT**<sup>™</sup>

#### **SURFACE KOATINGS, INC.**

134 Davis St. Portland, TN 37148  
 Phone: (615) 323-9461 Fax: (615) 323-9816  
 Visit us online at: [www.SurfKcoat.com](http://www.SurfKcoat.com)

## INSTRUCTIONS FOR USE

Preparation: Sweep the area to be cleaned free of trash and debris. Protect all areas not to be cleaned or stripped. Mask off all adjacent surfaces with painter's tape or plastic duct tape. If needed, use a plastic or coated cardboard as a spray shield.

1. Apply **Glu-Gone** by spray method liberally over glue/mastic concrete surface to be removed at an approximate coverage rate of 150-200 square feet per gallon. A stiff bristle brush should be used to agitate **Glu-Gone** into the adhesive.
2. Allow carpet remover to penetrate and emulsify coating for approximately 20-45 minutes depending upon area temperature and relative humidity.
3. A scraper should be used to remove emulsified adhesive. Heavily accumulated areas may also require a second treatment.
4. Flush the stripped area with water. Rinse and mop up or use a wet shop vac to remove existing coating.
5. Once dry, the floor is ready to apply coatings. If applying acid stain to existing concrete surface, use **Surf-Prep** to prepare the floor to be stained.

Please note: Glue and mastic can be trapped in the pores of a concrete surface. Mechanical means of profiling the floor may be necessary to apply some stains or coatings. Test prior to stain or coating application.

## CLEAN-UP

Use warm soap and water. Dispose of containers in accordance with local and federal regulations.

## PRODUCT REMOVAL

Not applicable.

## PRECAUTIONS AND LIMITATIONS

- ▶ **Glu-Gone** will freeze. It is recommended to store in an area between 50 F and 85 F recommended.
- ▶ **Glu-Gone** will only emulsify carpet glue and adhesive. Not recommended to strip acrylic, epoxies, or urethanes.
- ▶ All HVAC ventilation ducts should be somehow blocked prior to application so fumes are not distributed.
- ▶ **Glu-Gone** contains solvents such as Glycol Ethers. Abide by recommended safety guidelines.
- ▶ Coverage rates depend upon many conditions including application method, surface porosity, applicator, ect.
- ▶ **Glu-Gone** was designed for to remove mastic/glue deposits on interior surfaces.
- ▶ **Glu-Gone** should not be diluted. It is not water soluble and should not be mixed with solvents as well.

## SPECIAL NOTES

Please consult Material Safety Data Sheet (MSDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 615-323-9461.

**SURFKOAT™**

### **SURFACE KOATINGS, INC.**

134 Davis St. Portland, TN 37148  
Phone: (615) 323-9461 Fax: (615) 323-9816  
Visit us online at: [www.SurfKcoat.com](http://www.SurfKcoat.com)