

KOLOUR DYE

PRODUCT CODES: 007-DYE01 → 007-DYE20

Translucent, interior concrete dye available in 20 colors.

PRODUCT DESCRIPTION

Kolour Dye™ is a translucent dye, formulated using very fine particles of color designed to penetrate and color interior cementitious surfaces, including polished concrete. **Kolour Dye™** creates a unique, multi-colored translucent color scheme that unlike paints, will not crack, chip, or peel. **Kolour Dye™** is available in 20 standard colors but can be combined to create an unlimited color palate that creates a similar mottling or marbled effect, when used properly. Create the look of a beautiful, custom acid stained floor in about 1/3 of the time.

BENEFITS/FEATURES

- ◆ 20 great color choices in neutral and vibrant varieties.
- ◆ Very economical way to finish and beautify garage and basement floors.
- ◆ Kolour Dyed floors are a low maintenance alternative to many popular flooring systems.
- ◆ Provides a beautiful mottled effect similar to the likes of acid stains.

RECOMMENDED APPLICATIONS

Kolour Dye™ is recommended for most cured, unsealed interior concrete substrates. Do not apply to a floor that has been sealed prior until all sealer has been completely removed.

TECHNICAL INFORMATION

Solids.....n/a	Wet Appearance.....colored liquid
Drying Time.....approx. 1 minute	Dry Appearance.....colored powder
Re-Coat Time.....Refer to Directions	VOC Content.....0 g/l
Foot Traffic.....Refer to Directions	Blush Resistance..... n/a
Wheel Traffic.....Refer to Directions	Solvent Resistance.....n/a
Application Temp.....40°F - 85°F	Concrete Penetration.....Excellent

***Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

SPECIFICATIONS/COMPLIANCES

Kolour Dye™ are VOC and OTC compliant in all areas of the United States and many foreign nations.

APPROXIMATE COVERAGE RATES

<u>Application Surface</u>	<u>First Coat</u>	<u>Optional Second Coat</u>
New and Old (unsealed) concrete	600 - 700 ft ²	600 - 700 ft ²

*Coverage rates above reflect approximate coverage of finished product (per gallon) applied per instructions. Coverage rates will vary significantly and will be determined upon the surface porosity of the concrete as well as the application style.

SHELF LIFE

Kolour Dye™ has a shelf life of up to two years in it's original, sealed, unopened container.

PACKAGING

Kolour Dye™ are packaged and stocked in 4 oz (1 quart), 16 oz. (1 gallon), and 32 oz. (5 gallon) containers. (finished product)

SURFKOAT™

SURFACE KOATINGS, INC.

134 Davis St. Portland, TN 37148
 Phone: (615) 323-9461 Fax: (615) 323-9816
 Visit us online at: www.SurfKcoat.com

INSTRUCTIONS FOR USE

PREPARATION: Test areas are strongly recommended on the actual surface of the proposed application. Testing in several areas of the concrete will better determine suitability, coverage, and approximate final results. The application area should be clean and free from all forms of dirt, oil, alkali, paint, cure & seals, and any other form of contaminant. Protect all areas not to be dye accordingly. Apply Kolour Dye™ only to dry, neutral concrete surfaces.

MIXING: Kolour Dye™ is packaged only in a powder form which needs to be mixed with acetone in 1 quart, 1 gallon, or 5 gallon increments. Empty Kolour Dye™ into appropriate amount of acetone per instructions (this will depend on the size of the bottle purchased). Using the re-closable acetone container is recommended for mixing. Blend the mixture by stirring the open container, or by shaking the closed container for 30 seconds. Allow the mixture to dissolve for at least 3 hours prior to application. If a slower drying solution that will create a better mottled effect is desired, add the recommended amount of Kolour Dye™ Penetration and Mottling Agent at any time prior to application, per instructions. *Kolour Dye™ Penetration and Mottling Agent* is not recommended for porous concrete surfaces. Do not use any form of electrical equipment to mix the dye with the acetone. It is recommended to follow the manufacturer of the acetones instructions and the material safety data sheet (MSDS) for exposure limitations and safe handling practices.

APPLICATION: Apply Kolour Dye™ using an acetone sprayer with a #6 or #8 tip, keeping the tip approximately 24 inches from the surface. Apply in a uniform circular motion, not allowing the dye to puddle. The concrete surface should appear wet for just a few seconds when applied properly. Mop up any puddle or excess dye with a clean rag to allow the surface to dry evenly. Allow Kolour Dye™ to dry for approximately 1 minute. When using Kolour Dye™ in conjunction with polishing, apply the dye after polishing with a 400 grit resin. If needed, a second application of Kolour Dye™ may be applied prior to the final cycle.

CLEANING: Kolour Dye™ may leave residual dye on the surface after each application. It is recommended to dry buff using a buffer/burnisher with a white pad to remove loose dye. Vacuum or dust mop loose dye prior to sealing application. The use of water to clean and remove loose dye is not recommended. When polishing, neglecting to clean residual dye can affect resin performance.

SEALING: Seal Kolour Dye™ using a low viscosity, sprayable sealer. Use appropriate sprayer and tip per individual sealer instructions. Two coats are recommended for superior protection. It is not recommended to roll-on sealer over Kolour Dye™, as it may reactivate the dye. *2000 Supreme* or *Stamp Seal* are recommended sealers when using Kolour Dye™.

WAXING: When using a floor wax to polish, allow sealer to dry and completely cure for 3-4 days. Apply wax per manufacturer's specifications. *Cherry Surf-Wax* is our recommended floor wax.

CLEAN-UP

Use Xylene. Dispose of containers in accordance with local and federal regulations.

PRODUCT REMOVAL

Kolour Dye™ is a concrete dye and can not be chemically stripped. A commercial floor sander, diamond grinder, or another similar mechanical machine is necessary.

PRECAUTIONS AND LIMITATIONS

- ▶ **Kolour Dye™** will not freeze in storage, however, storage in areas between 50 F and 85 F is recommended.
- ▶ All HVAC ventilation ducts should be somehow blocked prior to application so solvent fumes are not distributed.
- ▶ **Kolour Dye™** is extremely flammable (finished product). Do not smoke.
- ▶ It is not recommended to apply **Kolour Dye™** over carpet, tile, and other types of floor adhesives.
- ▶ Coverage rates depend upon many conditions including application method, surface porosity, applicator, ect.
- ▶ **Kolour Dye™** was designed for interior concrete. It is not recommended for exterior applications.
- ▶ **Kolour Dye™** should only be sprayed. Refer to instructions above prior to use.
- ▶ It is recommended to seal over **Kolour Dye™** with UV Resistant coatings only.
- ▶ **Kolour Dye™** may be mixed to form various colors. Note, we cannot be held responsible for color outcome.
- ▶ **Kolour Dye™** is a permanent application. Please Test prior to use.

SPECIAL NOTES

Please consult Material Safety Data Sheet (MSDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 615-323-9461.

◆ For color selection, please request a color chart. FOR PROFESSIONAL USE ONLY!

SURFKOAT™

SURFACE KOATINGS, INC.

134 Davis St. Portland, TN 37148
Phone: (615) 323-9461 Fax: (615) 323-9816
Visit us online at: www.SurfKcoat.com