

RAW SOLVENTS

PRODUCT CODES: 009-AR100, 009-XYLNE, 009-ACTNE, 009-MSPIR

RAW SOLVENTS: AROMATIC 100, XYLENE, AND ACETONE

PRODUCT DESCRIPTION

Raw Solvents are used in various aspects of industry. *Aromatic 100, Xylene, Mineral Spirits* and *Acetone* are used in the paint and coatings manufacturing process. These solvents can be used for many various reasons such as paint and coating clean-up for tools and accessories, paint thinning, coating re-emulsification for purpose of fixing faulty applications or conditions, etc.

BENEFITS/FEATURES

- ◆ Superior cleaning capabilities and re-emulsification properties of solvent based coatings.

RECOMMENDED APPLICATIONS

Applications Vary

TECHNICAL INFORMATION

Solids.....	0%	Wet Appearance.....	Clear
Drying Time.....	Refer to Directions	Dry Appearance.....	n/a
Re-Coat Time.....	Refer to Directions	VOC Content.....	Varies
Foot Traffic.....	Refer to Directions	Blush Resistance.....	n/a
Wheel Traffic.....	Refer to Directions	Solvent Resistance.....	n/a
Application Temp.....	40°F - 85°F	Concrete Adhesion.....	n/a

***Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

SPECIFICATIONS/COMPLIANCES

Not Applicable

APPROXIMATE COVERAGE RATES

<u>Application Surface</u>	<u>First Coat</u>	<u>Optional Second Coat</u>
Varies	Varies	Varies

*Coverage rates vary depending upon surface porosity and texture, and application method. Follow directions for best results.

SHELF LIFE

Raw Solvents have a shelf life of one-two years in it's original, sealed, unopened container.

PACKAGING

Raw Solvents are packaged and stocked in 1 gallon cans, 5 gallon pails, and 55 gallon drums

SURFKOAT™

SURFACE KOATINGS, INC.

134 Davis St. Portland, TN 37148
 Phone: (615) 323-9461 Fax: (615) 323-9816
 Visit us online at: www.SurfKcoat.com

INSTRUCTIONS FOR USE

Instructions vary due to extensive amount of uses. Please contact the manufacturer for details pertaining to your specific application.

CLEAN-UP

Dispose of containers in accordance with local and federal regulations.

PRODUCT REMOVAL

Not applicable.

PRECAUTIONS AND LIMITATIONS

- ▶ **Raw Solvents** will not freeze during storage, however, allow temperature to rise to 50 degrees F prior to application.
- ▶ All HVAC ventilation ducts should be somehow blocked prior to application so solvents fumes are not distributed.
- ▶ Keep away from open flames. **Raw Solvents** are flammable and is very susceptible to ignition.
- ▶ Coverage rates depend upon many conditions including application method, surface porosity, applicator, ect.
- ▶ **Raw Solvents** can re-vitalize heavily coated old and deteriorated concrete sealer applications.
- ▶ **Raw Solvents** do not make existing coatings resistant to brake fluid, gasoline, and many similar products.

SPECIAL NOTES

Please consult Material Safety Data Sheet (MSDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 615-323-9461.

SURFKOAT™

SURFACE KOATINGS, INC.

134 Davis St. Portland, TN 37148
Phone: (615) 323-9461 Fax: (615) 323-9816
Visit us online at: www.SurfKcoat.com