

SURF-FILM CONCENTRATE

PRODUCT CODE: 010-SFCON

CONCENTRATED CONCRETE EVAPORATION RETARDANT & FINISHING AID

PRODUCT DESCRIPTION

Surf-Film Concentrate is a highly concentrated water based evaporation retardant and finishing aid for flat concrete work. **Surf-Film Concentrate** reduces the evaporation of surface moisture in warm, windy or dry conditions. **Surf-Film Concentrate** reduces drag or stickiness in the troweling process, therefore reducing the need for additional water during the finishing process.

BENEFITS/FEATURES

- ◆ Excellent lubricant for final finishing of concrete saving time and money.
 - ◆ Allows additional working time when troweling concrete
 - ◆ Very Economical Formulation due to high concentration

RECOMMENDED APPLICATIONS

Surf-Film Concentrate is recommended for interior or exterior fresh concrete surfaces where an evaporation retardant or finishing aid is needed.

TECHNICAL INFORMATION

Solids.....	n/a	Wet Appearance.....	yellow-green
Drying Time.....	n/a	Dry Appearance.....	n/a
Re-Coat Time.....	n/a	VOC Content.....	n/a
Foot Traffic.....	n/a	Blush Resistance.....	n/a
Wheel Traffic.....	n/a	Solvent Resistance.....	n/a
Application Temp.....	50°F - 90°F	Concrete Adhesion.....	n/a

***Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

SPECIFICATIONS/COMPLIANCES

No specifications noted

APPROXIMATE COVERAGE RATES

<u>Application Surface</u>	<u>First Application</u>	<u>Optional Second Application</u>
Freshly Placed Concrete	200-400 sq. ft. per gallon	200-400 sq. ft. per gallon

*Coverage rates vary depending upon surface porosity and texture, and application method. Follow directions for best results.

SHELF LIFE

Surf-Film Concentrate has a shelf life of one year in it's original, sealed, unopened container.

PACKAGING

Surf-Film Concentrate is packaged and stocked in 1 gallon jugs and 5 gallon pails, and 55 gallon drums.

SURFKOAT™

SURFACE KOATINGS, INC.

134 Davis St. Portland, TN 37148
 Phone: (615) 323-9461 Fax: (615) 323-9816
 Visit us online at: www.SurfKcoat.com

MISC. PRODUCTS

SURF-FILM CONCENTRATE

INSTRUCTIONS FOR USE

APPLICATION

Surf-Film Concentrate is a concentrated formula that should be diluted prior to application. Dilute 1:11 with clean water prior to use.

Apply Surf-Film Concentrate (diluted) with a pump-up garden sprayer or power sprayer. A fan tip of 0.010-0.018 is recommended. Spray a fine mist onto the surface of plastic concrete, preferably on the bleed water. Avoid applying Surf-Film Concentrate (diluted) in excessive quantities or creating puddles. Treated areas are easily distinguished by a fugitive dye. Once the surface has dried, the color will disappear.

For dry shake applications, Surf-Film Concentrate (diluted) may be applied to the surface before and after the material is spread onto the surface. Do not apply Surf-Film Concentrate (diluted) once the dry shake begins the initial set.

CLEAN-UP

Use warm soap and water. Dispose of containers in accordance with local and federal regulations.

PRODUCT REMOVAL

Not Applicable.

PRECAUTIONS AND LIMITATIONS

- ▶ **Surf-Film Concentrate** will freeze. It is recommended to store in an area between 50 F and 80 F recommended.
- ▶ **Surf-Film Concentrate** is harmful if swallowed. Abide by recommended safety guidelines.
- ▶ Usage rates depend upon many variables including dilution rate, cement mixture, etc.
- ▶ **Surf-Film Concentrate** was designed for interior and exterior use.

SPECIAL NOTES

Please consult Material Safety Data Sheet (MSDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 615-323-9461.

SURFKOAT™

SURFACE KOATINGS, INC.

134 Davis St. Portland, TN 37148
Phone: (615) 323-9461 Fax: (615) 323-9816
Visit us online at: www.SurfKcoat.com